

USER INTERFACE

- . TACTILE SELECTION PANEL WITH 8 SELECTIONS FOR HOT BEVERAGES and 3 selections for water.
- . THE SELECTION PANEL OFFERS A TRUE INTERACTIVE COMMUNICATION SPACE THAT ALLOWS TO SPREAD VIDEOS OR MESSAGES, TO CHANGE THE ICONE AND TO PERSONALIZE THE MENU IN A SIMPLY WAY.
- . COFFEE DELIVERY AREA: 17 CM HIGH DELIVERY AREA SUITABLE FOR MUG OR JUG AND FOLDAWAY ESPRESSO CUP SUPPORT.
- . WATER DELIVERY AREA: 22 CM HIGH DELIVERY AREA SUITABLE FOR CUPS, BOTTLES OR JUG AND FOLDAWAY CUP SUPPORT.
- . 2 MANUAL CUP DISPENSERS WITH A CAPACITY OF 2x60 CUPS (DIAM 70-73 MM).
- . MODERN AND SMART DESIGN.
- . IN COMPLIANCE WITH STANDARD OF ACCESS FOR DISABLED PEOPLE.



TECNOLOGIE



LED, LOW VOLTAGE LIGHTING



SENSOR DETECTION CUP (OPTION)



PATENTED ESPRESSO GROUP




ENERGY SAVING MOD (OPTION)



FIREWALL UV SENSOR



DUO. BE THE ONE, COFFEE & WATER.





SPECIFICATIONS

ELECTRICAL SUPPLY

220-240 Vac / 50 Hz

INTERNAL ELECTRICAL SUPPLY

All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistance, that is at 230 Vac - 50 Hz or 120 Vac - 60 Hz

POWER SUPPLY

2.7 Kw double boiler espresso version

WATER SUPPLY

Fitting connection = 3/4" Water pressure = 0.5 - 6.5 bar

SYSTÈME WATERLOGIC

- Capacity chilled water dispenser: 1.2 lt/min (on the CO, version).
- Carbonartor for chilled water.
- UV lamp system of purification of the water.
- Compressor: 130 W. • UV lamp: 15 W. · Total unit: 190 W.
- CO₂ bottle: 4 kg.
- Refrigeration gas R134A: 45g.
- Granular Activated Carbon filters (10° CBC 1 Micron).



DUO	
FSPRFSS0	

1.	COFFEE	
2.	CHOCOLATE	
3	MII K	

WATER SELECTIONS

AMBIENT WATER COLD WATER 3. SPARKLING WATER

HOT BEVERAGES SELECTIONS

- 1. SHORT COFFEE
- 2. LONG COFFEE 3. WHITE COFFEE
- . CAPPUCCINO . MOCACCINO
- 6. CHOCOLATE
- 7. STRONG CHOCOLATE

VERSIONS DUO

TOUCH ESPRESSO DOUBLE BOILER COFFFF BEANS 1

DIMENSIONS

INSTANT CANISTERS

2 (1 mixer) H * 1231 mm x W 817 mm x D 512 mm WEIGHT 60 kg

DUO E2S

FEATURES

- Available in mains water supply system version (POU Point Of Use).
- Uppers doors for coffee and water part with safety look.
- The machine is equipped with 4 wheels (2 with brake) for simplified handling.

HOT BEVERAGES DISPENSER

- Bianchi patented expresso group.
- Mixers are extractable to make maintenance operations easier.
- Liquid waste tray: 1 litre with visible signal for maximum water level
- Coffee waste tray: 60 pods with counter software management.
- Pivoting roof for loading products. The roof is locked when the upper door is closed.
- Ready for installation of a water filter.

WATER DISPENSER

- Equipped with the Waterlogic FirewallTm purification system which provides the highest level of drinking water hygiene.
- Removable tray for carrying drinks on the left side of the
- Water side: pivoting roof for the storage of products.

PRODUCT CAPACITY

Coffee beans 0.80 kg (14 lt) Milk 0.55 kg (1.75 lt) Chocolate 1.30 kg (1.75 lt)

PAYMENT SYSTEM

- Compatible with a standard validator (parellele 24 V or 12 V) or a cashless system EXE or MDB.
- The payment system can manage the water and/or the coffee part.

ACCESSORIES KIT

- Cup sensor for both cup station (without cups the machine doesn't deliver the product).
- Cup stations (coffee part and water part) lighting kit through by software.
- RS232 module.
- Visual Smart Programmer Speed that allows the upload of the firmware and settings and the download of the settings and audit without a PC.
- Module free vend.
- IRDA interface
- Flash USB interface.
- Clock chip.
- Coin introduction kit.

BENEFITS OF THE CONCEPT

- Convergence of 2 machines in a single integrated system simple and easy to use.
- Reduction of the carbon footprint: 1 machine instead of 2, less consumption of energy and fuel for transport compared to 2 machines
- Single water purified circuit also for coffee.
- Available in mains water supply system version: no waste of plastic
- Convenient, easy to use and easy to clean.
- The machine offers excellent branding opportunities.
- Rationalization, service, and competitive advantage.

ENVIRONMENT

- Energy saving mod with programmable periods to reduce the energy cunsumption when the machine is in stand by.
- In compliance with RHOS and WEEE.





^{*} with wheel H 58.4 mm included