BVM 952

USER INTERFACE

- . DIRECT SELECTION PANEL WITH 26 PUSH BUTTONS THAT CAN BE CONFIGURED BOTH AS SELECTIONS OR PRE-SELECTIONS.
- . CUSTOMIZABLE SUGAR DOSAGE.
- . END SELECTION ACOUSTIC SIGNAL.
- . 32 DIGIT ALPHANUMERIC DISPLAY.
- . SLOW FALLING PRODUCT DISPENSING DOOR.
- . DESIGN MODERN WITH UPPER LEXAN BACKLIGHTED THAT OFFERS EXCELLENT BRANDING OPPORTUNITIES.
- . IN COMPLIANCE WITH STANDARD OF ACCESS FOR DISABLED PEOPLE.



BVM 952 + VISTA M

TECHNOLOGY



LED, LOW VOLTAGE LIGHTING



GCS, PATENTED GRINDING CONTROL SYSTEM (OPTION)



PATENTED GPRS TELEMETRY SYSTEM (OPTION)



SENSOR DETECTION CUP (OPTION)



PATENTED ESPRESSO GROUP




ENERGY SAVING MOD (OPTION)



THE COMPACT MACHINE FOR AROMATIC ESPRESSO AND CREAMY BEVERAGES.


BVM 952, automatic 500 cups vending machine for hot and cold drinks with up to 48 programmable selections and direct selection panel with 26 push buttons.






ESPRESSO

SUGAR 5. CHOCOLATE DECAFFEINATED 6. MILK 7. INSTANT 3. TEA 4. COFFEE




ESPRESSO DOUBLE COFFEE BEAN CANISTER E4S

2. DECAFFEINATED 6. CHOCOLATE 3. COFFEE 1 4. COFFEE 2 7. MILK



ESPRESSO DOUBLE COFFEE BEAN CANISTER ESS

INSTANT CHOCOLATE 3. COFFFF: MILK 8. DECAFFEINATED 4. COFFFF 2



INSTANT

1. SOUP 2. TEA 3. SUGAR	5. DECAFFEINATED 6. CHOCOLATE 7. MILK
4 COFFFF	

VERSIONS BVM 952	E5S ESPRESSO SINGLE BOILER *	E5S ESPRESSO DOUBLE BOILER *	E4S ESPRESSO SINGLE BOILER DOUBLE COFFEE BEAN CANISTER *	E5S ESPRESSO SINGLE BOILER DOUBLE COFFEE BEAN CANISTER *	I7S INSTANT *
COFFEE BEANS	1	1	2	2	-
SUGAR CANISTER	1	1	1	1	-
INSTANT CANISTERS	5	5	4	5	7

DIMENSIONS

H 1630 mm x W 666 mm x D 776 mm WEIGHT 150 kg * models available also with anti-vandal coin introduction (IAV)

BVM 952 SPECIFICATIONS

ELECTRICAL SUPPLY

230 Vac - 50 Hz / 120 Vac - 60 Hz

INTERNAL ELECTRICAL SUPPLY

All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances, the pump and the steam ventilator that are at 230 Vac – 50 Hz or 120 Vac – 60 Hz

POWER SUPPLY

1.80 kW single boiler espresso version 2.35 kW double boiler espresso version 2.20 kW instant version

WATER SUPPLY

Fitting connection = 3/8" Water pressure = 0.5 - 6.5 bar

FEATURES

- Reinforced cabinet with anti-vandal hinges and door look with programmable code.
- Mixers and boiler assembly are extractable to make maintenance operations easier.
- Standard serpentine kit for tea on all versions.
- Cup dispenser adjustable to various diameters (from 70 to 74 mm) and dispenser for 90 or 105 mm stirrers.
- Switching power supply that guarantees total stability of the instant product dose and complete electric safety protections.
- Standard multi-protocol electronics.

PRODUCT CAPACITY

Coffee beans 3.8 kg Double coffee bean canister 2.5 kg each (x2) Instant coffee 1.2 kg * 1.25 kg Barley Powder milk 1.7 kg Whitener 3.2 kg Chocolate 3.6 kg Lemon tea 3.3 kg Tea 1.7 kg Soup 3.6 kg * In the double coffee bean Sugar 4.0 kg canister versions additional Spoons 400 pcs decaffeinated canister with Cups 500 pcs 0.34 kg capacity.

PAYMENT SYSTEM

- Compatible with all system of payment available on the market.
- Can work in master/slave with only one set of payment systems on the hot vending machine together with a refrigerated automatic spiral vending machine for the sale of snacks, cans and bottles, increasing selling opportunities.

ACCESSORIES KIT

- Cup sensor.
- Antivandal coin introduction.
- Kit chip clock (for energy saving mod and promotional activities).
- RS232 module.
- Visual Smart Programmer Speed that allows the upload of the firmware and settings and the download of the settings and audit without a PC.
- Cooling unit for cold instant beverages.
- Telemetry kit (GPRS modem with antenna + clock chip).
- · Cup stations lighting kit through by software.
- System for the automatic regulation of the coffee bean grinding that guarantees with the variations of the humidity and the temperature, the best quality of the product dispensed at all times.
- Additional canister and mixer to reach 6 canisters configuration in the espresso version (sugar in addition) and 8 canisters in the instant version.

FNVIRONMENT

- Backlighted lexan with led to reduce energy consumption and with a lifetime greater than neon.
- Compatible with paper cups and wooden spoons.
- OPTION: cup sensor to reduce the consumption of plastic cups and to deliver a beverage in a mug.
- OPTION: energy saving mod to reduce the energy cunsumption when the machine is in stand by.
- In compliance with RHOS and WEEE.



