

LEI 600 PP

► www.bianchivending.com

USER INTERFACE

- . DIRECT SELECTION PANEL WITH 13 VISIBLE AND INTUITIVE PUSH BUTTONS OF WHICH 10 ARE DIRECT SELECTIONS, 1 PRE-SELECTION (THAT CAN BE CONFIGURED AS SELECTION) AND 2 PUSH BUTTONS FOR SUGAR DOSAGE.
- . CUSTOMIZABLE SUGAR DOSAGE.
- . END SELECTION ACOUSTIC SIGNAL.
- . 32 DIGIT ALPHANUMERIC DISPLAY.
- . SLOW FALLING PRODUCT DISPENSING DOOR.
- . DESIGN MODERN WITH UPPER LEXAN BACKLIGHTED THAT OFFERS EXCELLENT BRANDING OPPORTUNITIES.
- . IN COMPLIANCE WITH STANDARD OF ACCESS FOR DISABLED PEOPLE.



LEI 600 PP + VISTA L

TECHNOLOGY



LED, LOW VOLTAGE
LIGHTING



GCS, PATENTED GRINDING
CONTROL SYSTEM (OPTION)



PATENTED GPRS TELEMETRY
SYSTEM (OPTION)



SENSOR DETECTION
CUP (OPTION)



PATENTED
ESPRESSO GROUP



ENERGY SAVING
MOD (OPTION)



A MODEL THAT COMBINES QUALITY AND SIMPLICITY
FOR A CORE ASSORTMENT PRODUCT OFFER.

LEI 600 PP (flute door), automatic vending machine for hot drinks with 600 cups capacity and 13 selection buttons of which 3 pre-selections (2 for sugar setting + 1 for decaffeinated in the standard version).



LEI 600 PP SPECIFICATIONS

ELECTRICAL SUPPLY

230 Vac – 50 Hz / 120 Vac – 60 Hz

INTERNAL ELECTRICAL SUPPLY

All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances, the pump and the steam ventilator that are at 230 Vac – 50 Hz or 120 Vac – 60 Hz

POWER SUPPLY


1.80 kW single boiler espresso version

2.20 kW instant version

WATER SUPPLY


Fitting connection = 3/4"

Water pressure = 0.5 – 6.5 bar



LEI 600 PP
ESPRESSO

- | | |
|------------------|--------|
| 1. SUGAR | 5. MLK |
| 2. DECAFFEINATED | 6. TEA |
| 3. COFFEE | |
| 4. CHOCOLATE | |



LEI 600 PP
INSTANT

- | | |
|-----------|------------------|
| 1. SOUP | 5. DECAFFEINATED |
| 2. TEA | 6. CHOCOLATE |
| 3. SUGAR | 7. MILK |
| 4. COFFEE | |

VERSIONS LEI 600 PP	E4S ESPRESSO SINGLE BOILER *	I7S INSTANT *
COFFEE BEANS	1	-
SUGAR CANISTER	1	-
INSTANT CANISTERS	4	7
DIMENSIONS	H 1830 mm x W 620 mm x D 770 mm WEIGHT 140 kg	
	* models available also with anti-vandal coin introduction (IAV)	

FEATURES

- Reinforced cabinet with anti-vandal hinges and door lock with programmable code.
- Mixers and boiler assembly are extractable to make maintenance operations easier.
- Standard serpentine kit for tea on all versions.
- Cup dispenser adjustable to various diameters (from 70 to 74 mm) and dispenser for 90 or 105 mm stirrers.
- Switching power supply that guarantees total stability of the instant product dose and complete electric safety protections.
- Standard multi-protocol electronics.

PRODUCT CAPACITY

Coffee beans	3.80 kg *
Decaffeinated coffee	1.40 kg
Barley	1.50 kg
Milk	2.20 kg
Creamer	4.00 kg
Chocolate	4.80 kg
Lemon tea	5.20 kg
Tea	2.40 kg
Soup	3.80 kg
Sugar	5.20 kg
Spoons	600 pcs.
Cups	600 pcs. (can be increased up to 700)

* fitting an extension can catch up with 4.50 kg

PAYMENT SYSTEM

- Compatible with all system of payment available on the market.
- Can work in master/slave with only one set of payment systems on the hot vending machine together with a refrigerated automatic spiral vending machine for the sale of snacks, cans and bottles, increasing selling opportunities.

ACCESSORIES KIT

- Cup sensor.
- Antivandal coin introduction.
- Kit chip clock (for energy saving mod and promotional activities).
- RS232 module.
- Visual Smart Programmer Speed that allows the upload of the firmware and settings and the download of the settings and audit without a PC.
- Telemetry kit (GPRS modem with antenna + clock chip).
- System for the automatic regulation of the coffee bean grinding that guarantees with the variations of the humidity and the temperature, the best quality of the product dispensed at all times.

ENVIRONMENT

- Backlighted lexan with led to reduce energy consumption and with a lifetime greater than neon.
- Compatible with paper cups and wooden spoons.
- OPTION: cup sensor to reduce the consumption of plastic cups and to deliver a beverage in a mug.
- OPTION: energy saving mod to reduce the energy consumption when the machine is in stand by.
- In compliance with RHOS and WEEE.



Bianchi Vending Group • info@bianchivending.com

Corso Africa 9, 24040 Zingonia di Verdellino, Bergamo, Italia tel. +39.035.45.02.111, fax. +39.035.883.304

Specifications and technical information given are indicative and may be subject to change without prior notice. ZD-LEI 600 PP-ED10/2012/EN