

### CBS-2032s EXTRACTOR® Brewer Series

Pulse-Brew Intermittent Spray Shower technology with programmable brew volume • brew time • bypass

- pre-wet percent • pre-wet delay • drip delay
- brew basket lock

All the great programmable parameters of the EXTRACTOR® CBS-2030e series plus square brew baskets, bypass and brew basket lock. Brews directly into 1.0 gallon LUXUS® L3S-10 dispenser or a 3.0L airpot.

FETCO's commitment to developing ecology-friendly technology is top priority. FETCO® equipment does not contain mercury, lead or fiberglass. Instead, we use solid state relays, stainless steel fittings and insulation that does not contain harmful materials.



**CBS-2032s** with 2  
LUXUS® L3S-10  
dispensers



S Series now comes standard with Cascading Spray Dome™.



**Water Specifications**

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	.5	20-75

**Measurements**

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
26	19	18 1/4	53	64

**Standard Electrical Configurations**

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour (1)	
							cold water	hot water
E32015S	2x3.0 KW	120/208	1	3+G	4.6	22.4	14.6	22.0
		120/220			5.1	23.7	16.9	22.0
		120/240			6.1	25.8	19.4	22.0

Specifications subject to change without notice.

(1) Based on factory settings: 4.0 minute brew time:  
prewet: 200°F water

