

CBS-2052e20 **EXTRACTOR® Brewer Series**

Pulse-Brew Intermittent Spray Shower technology
with programmable brew volume • brew time •
pre-wet percent • pre-wet delay • drip delay

FETCO's double 2.0 gallon EXTRACTOR® Brewer is built for high volume performance. Dependable and reliable. That's how our satisfied customers describe this hard-working coffee brewer. The CBS-2052e20 brews directly into the following 2.0 gallon dispensers: L3D-20, L3S-20, LD-20 and LS-20.

FETCO's commitment to developing ecology-friendly technology is top priority. FETCO® equipment does not contain mercury, lead or fiberglass. Instead, we use solid state relays, stainless steel fittings and insulation that does not contain harmful materials.



E Series now comes standard with
Cascading Spray Dome.™



Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	1.5	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
39 3/8	21 7/8	19 1/8	95	102

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour (3)	
							cold water	hot water
E53016(1)	2x3.0 KW(2)	120/208	1	3+G	4.6	22.4	7.7	18.6
		120/220			5.1	23.7	8.9	21.0
		120/240			6.1	25.8	10.3	22.0
	3x3.0 KW	120/208	3	4+G	6.9	19.5	11.5	22.0
		120/220			7.7	20.6	13.4	22.0
		120/240			9.1	22.5	15.4	22.0
E53026(1)	2x5.0 KW	120/208	1	3+G	7.6	36.9	12.8	22.0
		120/220			8.5	39.0	14.9	22.0
		120/240			10.1	42.5	17.1	22.0
	3x5.0 KW(2)	120/208	3	4+G	11.4	32.0	19.2	22.0
		120/220			12.7	33.9	22.0	22.0
		120/240			15.1	36.9	22.0	22.0
*E52036	2x3.0 KW	220/240	1	2+G	5.1/6.1	23.7/25.8	10.3	22.0
*E52046	3x3.0 KW	220/380	3	3+G	12.7	19.3	22.0	22.0
*E52056	3x3.0 KW	240/415	3	4+G	15.1	21	22.0	22.0

*EXPORT ONLY

Specifications subject to change without notice.

(1) Universal wiring/ Multi- phase wiring

(2) Factory Setting

(3) Based on standard factory settings:

4.0 minute brew time: 9% pre-wet: 200° Water

