

CBS-62H 3.0 Gallon Coffee Brewer Volume Coffee at Your Fingertips

- Patented Gravity Dispense Tube System resists lime build up provides dependable performance
- Holds a constant water temperature during 100% of brew cycle
- Maintains sprayover volume consistency
- Utilizes all solid state components



CBS-62H with two
TPD-3.0 LUXUS® dispensers



Dual brew basket safety locks
incorporated into start switch



Stainless steel gourmet-size brew
baskets designed for heavier
brew ratios



Brews directly into our 3.0 gallon
LUXUS® TPD Dispensers

The LUXUS® TPD-Style Dispenser

FETCO's TPD-style dispensers are portable and require no electric power. Once filled and capped, it goes anywhere...Ready to act as your remote dispensing station wherever needed.



LUXUS® TPD-30

Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	2.0	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
40	35 1/2	22 3/8	195	197

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour ⁽¹⁾	
							<i>cold water</i>	<i>hot water</i>
C62016	3x3.0 KW	120/208	1	3+G	6.9	33.3	5.6	12.9
		120/220			7.7	35.2	6.5	14.9
		120/240			9.1	38.3	7.4	17.2
C62026	3x4.0 KW	120/208	1	3+G	9.1	44.1	7.4	17.2
		120/220			10.3	46.6	8.6	18.0
		120/240			12.1	50.8	9.9	18.0
C62036(1)	3x3.0 KW	120/208	3	4+G	6.9	19.5	5.6	12.9
		120/220			7.7	20.6	6.5	14.9
		120/240			9.1	22.4	7.4	17.2
C62046(1)	3x4.0 KW	120/208	3	4+G	9.1	25.8	7.4	17.2
		120/220			10.3	27.3	8.6	18.0
		120/240			12.1	29.7	9.9	18.0
C62056(1)	6x3.0 KW	120/208	3	4+G	13.6	38.3	11.2	18.0
		120/220			15.3	40.5	12.9	18.0
		120/240			18.1	44.1	14.9	18.0
C62066(1)	6x4.0 KW	120/208	3	4+G	18.1	50.8	14.9	18.0
		120/220			20.4	53.7	17.3	18.0
		120/240			24.1	58.5	18.0	18.0
C62146(1)	6x3.0 KW	480	3	3+G	18.1	22.5	14.9	18.0
C62166(1)	6x4.0 KW	480	3	3+G	24.1	29.7	18.0	18.0
** C62106(1)	6x3.0 KW	220/380	3	4+G	15.2	23.4	14.9	18.0
** C62136(1)	6x4.0 KW	220/380	3	4+G	20.3	31.3	18.0	18.0
** C62176(1)	6x3.0 KW	240/415	3	4+G	18.1	25.5	14.9	18.0

Specifications subject to change without notice

(1) Requires three phase upchange (z056)

*Based on standard factory settings : 4.0 minute brew time, 0% prewet, 200°F water

**EXPORT ONLY

