



CBS-71A with 6.0 gallon LBD-6 dispenser



CTR-71 Counter

CBS-71A

Single 6.0 Gallon Coffee Brewer

High-Volume Brewing

Single high volume brewer and one 6.0 gallon LUXUS® dispenser on a stationary counter. The large spray pan provides full and even saturation of the coffee bed along with the adjustable contact time and bypass features to extract the perfect cup of coffee, with a push of a button.

Adjustable Programming Parameters:

- Brew Temperature
- Brew Wait
- Bypass Percent
- Drip Delay
- Brew Orifice Size*

*Non-standard brew orifice sizes must be ordered from FETCO®



LUXUS® LBD-6 dispenser with drip tray

Model	Gallons/Hr	Oz/Hr	8 oz Cups/Hr	12 oz Cups/Hr	16 oz Cups/Hr	20 oz Cups/Hr
CBS-71A	18.0-30.0	2,304-3,840	288-480	192-320	144-240	115-192

Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	3.0	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
48 1/2	18	37	239	313

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour cold water
C71017	3x5.0 KW	120/208	3	4+G	11.5	33.3	3.0
		120/220			13.3	36.0	3.3
		120/240			15.2	37.9	3.6
C71027	3x10 KW	120/208	3	3+G	22.7	64.3	4.5
		120/220			26.3	70.3	4.8
		120/240			30.2	74.0	5.0
C71038	3x10 KW	120/480	3	3+G(1)	30.2	37.9	5.0
*C71058	*3x5.0 KW	220/240	3	4+G	12.9	33.9	3.6
*C71068	*3x10 KW	240/415	3	4+G	25.6	67.3	5.0

Specifications subject to change without notice

(1) Plus 120V cord and plug

*EXPORT ONLY

