

CBS-72AC

Twin 6.0 Gallon Coffee Brewer High-Volume Brewing

Simply brew directly into our 6.0 gallon, 18 gallon or 24 gallon On-The-Go Mobile LUXUS® Thermal Dispensers that can easily be wheeled anywhere hot or cold fresh beverages are needed.

Each CBS-72AC is actually 2 separate brewers in one body. Each side has its own water tank and three heaters.

Adjustable Programming Parameters:

- Brew Temperature
- Brew Wait
- Bypass Percent
- Drip Delay
- Brew Orifice Size*

*Non-standard brew orifice sizes must be ordered from FETCO®



CBS-72AC with two
LUXUS® LBD-6C dispensers



LUXUS® LBD-18 dispenser



LUXUS® LBD-24 dispenser

Model	Gallons/Hr	Oz/Hr	8 oz Cups/Hr	12 oz Cups/Hr	16 oz Cups/Hr	20 oz Cups/Hr
CBS-72AC	28.2-60.0	3,609-7,680	451-960	300-640	225-480	180-384

Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	3.0	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
79	36	35	564	669

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour cold water
C72018(1)	3x5.0 KW(3)	120/208	3	4+G	11.6	33.7	4.7
		120/220			13.4	36.7	5.4
		120/240			15.3	38.6	6.2
C72028(2)	3x5.0 KW(3)	120/208	3	4+G	22.8	65.0	6.0
		120/220			26.4	71.0	6.6
		120/240			30.3	74.7	7.2
C72038(1)	3X10 KW(3)	120/208	3	4+G	22.8	65.0	9.3
		120/220	3	4+G	26.4	71.0	10.0
		120/240	3	4+G	30.3	74.7	10.0
C720487(1)	3X10 KW (3)	120/480	3	3+G(4)	30.3	37.9	10.0
C72058(2)	3X10 KW (3)	120/480	3	3+G(4)	60.3	74.7	10.0
*C72108	3X5.0KW (3)	220/240	3	4+G	12.9	33.0	7.2
*C72118	3X10 KW (3)	240/415	3	4+G	25.6	67.3	10.0

Specifications subject to change without notice

- (1) With power management
- (2) Without power management
- (3) On each side
- (4) Plus 120V cord and plug
- *EXPORT ONLY

