

Elegant Efficient Professional



Espresso - Tall CUP





X-one

- ← Thermosiphon boiler: 2 groups = 13 L and 3 groups = 19.5 L
- ☐ Temperature stability: boiler controlled electronically, PID system
- Solution New coffee group: quality of extraction, consistency of the result in the cup
- ☐ Adjustable flow control to regulate temperature of the 1st coffees
- ← 2 steam harms double use: up (normal steam flow), down (quick spray)
- ⊆ Eco mode
- ← Automatic cleaning cycles (Alarm programmable)
- ⊆ Easy access to the main parts of the machine
- ← 1 Stopping tap per group allowing isolation of each group
- Single phase = 3500 watts. Option: three phase = 4200 watts, convertible in 2800 watts
- ACCESSORIES: 1 porter filter one cup / machine, 1 porter filter two cups / group, 1 test of water hardness, 1 cleaning filter, drain pipe and inlet hose.

COLORS AVAILABLE

Black

White

OPTIONS

 ⊆ Electrical cup
 warmer
 ⊆ Solo kit
 (water container)
 ⊆ New stainless
 steel cappuccinatore

MODEL	Width	Height	Depth	Boiler	Power	Voltage
2	768 mm	553 mm	527 mm	13 L	3500 W	230 V
3	983 mm	553 mm	527 mm	19.5 L	6000 W	400 V

