

by Instruments of Espresso





phonica













## phonica

28 Dale Street Brookvale NSW 2100 **T** 02 9938 1233 **F** 02 9905 3794 **E** info@orchestrale.com.au orchestrale.com.au



by Instruments of Espresso

TECHNICAL FEATURES	AUTOMATIC	Semi Automatic	
Automatic espresso coffee and cappuccino machine with programmable portion control			
Semiautomatic espresso coffee and cappuccino machine with continous coffee brewing			
Available in 1gr, 2 gr compact, 2 and 3 gr			
Coatchwork in pure polished and glazed stainless steel.Clear polycarbonate finish			
Boiler and pipes made in copper and brass pipe fittings			
Dual gauges for boiler and pump pressure control			
Visual boiler water gauge (on 1gr ,2 and 3 gr)			
Automatic water refill A.W.R. on 1gr , 2 and 3 gr (built with also manual refill)			
Boiler tap for manual dicharge			
Built-in motor pump (on request the motor pump can be outside)			
2 swivelling stainless steel steam wands with manual control			
1 swivelling stainless steel hot water wand with automatic and programmable water dosing controls			
1 swivelling stainless steel hot water wand with manual control on ( $1gr$ , $2gr$ compact auto ) and ( on $1gr$ , $2gr$ compact, $2\&3gr$ semi)			
Touch pad for coffee delivery for each group: -6 programmable selections with volumetric dosing -1 touch pad control for programming independent coffee dosages for each group Version with also 1 or 2 manual switch for semiautomatic brewing	•		
Electromechanical switch to dose the coffee serving for each group			
LED indicator to inform about the working selection			
Electronic cup-warmer on 2 and 3 groups automatic version			
LED indicator to inform the machine and cup-warmer is ON			
Back panel neon lighted with switch ON/OFF			

OPTION ON REQUEST	
Neutral back panel	
Electric cup-warmer	
Mixed hot water outlet	
Outside motor pump	
Raised group	
Cappuccino maker	
Milk frothing wand	
Counting systems	
Serial interface fo external connection	

TECHNICAL INFO	RMATIONS	1 GR	2 GR	2 GR COMPACT	3 GR
Power	W	2100/3100	2500/3900	2900	5560
Voltage	V	120 - 230 - 240 - 400 (2F-3F) / 50-60Hz			230-240-400(3F)/50-60Hz
Caldaia/Boiler	Lt	6	12	7	17
Width	mm	620	830	620	1060
Depth	mm	560	560	560	560
Height	mm	620	620	620	620
Net weight	Kg	70	84	78	100

 $The \ manufacturer \ reserves \ the \ right \ to \ modify \ the \ appliances \ presented \ in \ this \ pubblication \ whithout \ notice$ 











